

### **T70569** Coil Spring Compressor

- Compresses coil springs for strut services
- Heavy-duty steel construction
- Suitable for most import and domestic passenger vehicle spring sizes



### **T70570** Coil Spring Compressor

- Drop forged steel jaws
- Hardened alloy steel center bolts
- Compresses coil springs for strut services
- Suitable for passenger cars and light duty trucks
- Use with a 1/2" Dr. ratchet or 15/16" wrench



### **T70573** MacPherson Strut Compressor

- Compresses MacPherson strut spring sets when replacing strut shock absorbers
- Heavy-duty steel construction
- Can be used with hand or impact tools
- Fits most MacPherson struts and coil springs



### **T70574** Mini Coil Compressor

- Features two spring compressors that fit most vehicles with coil suspension
- Designed to be used in pairs on one coil spring to adjust lift or load bearing properties



### **T75506** MacPherson Strut Coil Spring Compressor

This tool was designed to instantly compress and hold



MacPherson strut coil springs for strut work servicing. It has a universal fit, applying to all spring thicknesses. The U-bolts lock the spring into position, assuring a safe environment for operation. Can be used with the GM W-Body Strut Service Kit (T75505).

### **T75762** MacPherson Strut Spring Hook Compressor Set



Efficiently compresses most MacPherson strut springs for shock absorber replacement. Designed with wide contact surfaces for variable coil sizes. Detent latch provides additional spring lock. Twin assembly allows rapid servicing by alternating from one set to the other.

Contents:  
2 sets of heat-treated alloy thrust screws 5/8" x 11 x 12" with forged hooks

### **T75761 Coil Spring Compressor**

This tool



on all passenger cars and pickup trucks with removable shock absorbers. It works on all springs up to 5-5/8" outer diameter and can grasp any wire spring up to a diameter of 3/4". Applicable to both straight or curved springs

### **T75528 Universal Strut Spring Compressor**

This tool kit is designed to compress and hold



MacPherson strut coil springs for strut work servicing. No special adaptor shoes needed. Features a universal fit, applying to a wide range of struts. Compresses springs of 4" to 9" outside diameter with wire diameters of 7/16" to 11/16". Safety lock pins hold compressor jaws in place, ensuring a safe environment for operation. Tool can be used by hand or driven by an impact wrench. Easily services strut on work bench or directly on the vehicle. Kit can be used with T75529 Alignment Assist Tool.

### **T75529 Camber Adjusting Tool**

Alleviates the task of adjusting the camber on most GM



and some Chrysler FWD vehicles by eliminating the need of a second person to hold the wheel. The tool holds it for you by simply resting on the tire and pushing against the strut.

#### Applications:

GM, Chrysler with slotted strut mounts. Please note that applications do not include the vehicles with rear air suspensions: Pontiac Bonneville, Olds '88 & '98, Buick Park Avenue and Cadillac Fleetwood

### **T75515 GM10 Strut Tool**

Includes:



- Double-ended spanner socket
- 3 lug - Jounce bumper retainer wrench
- 4 lug - Strut cap nut wrench
- Extension rod with 1/2" square drive
- T50 Star bit socket

Directly removes and installs oil-filled or gas-charged strut cartridges through the strut tower while it's still attached to the car. The double-ended spanner socket can be used as a jounce bumper retainer wrench or a strut cap nut wrench. The former is capable of removing or replacing the retainer from the strut, while the latter is capable of removing or replacing the strut cap nut from the strut cartridge. The star bit socket gains access to the strut by removing the top strut nut without winding the strut rod. No damage is imposed upon strut components during use.

#### Applications (GM10 models):

1988 to current Buick Regal, Grand Prix and Cutlass Supreme  
1990 to current Chevrolet Lumina

### T70301 Reversible 3-Jaw Oil Filter Wrench

- 3-Jaw
- removing spin-on type oil filters in confined spaces
- Serrated legs wrap around oil filter
- Capacity: 64-120mm (2-1/2" to 4-3/4")



### T70303 Universal 3-Jaw Filter Wrench

- 3-Jaw
- car or light truck
- Heat-treated, carbon steel, black oxide finish
- Jaw capacity 63-99mm (2-1/2" to 3-7/8")



### T70306 Reversible 3-Jaw Oil Filter Wrench

- Feature
- most cars and light trucks
- Chrome and black oxide finish
- Capacity: 64-102mm (2-1/2" to 4")



### T70308 Reversible Oil Filter Wrench

- Secure
- Spring loaded reversible cam action design allows easy installation or removal of oil filters
- Use with a 3/8" Dr. wrench



### T70310 Swivel Handle Oil Filter Wrench

- 90-deg
- Blackened wide band resists corrosion and prevents the filter from being crushed
- Dimples on band and vinyl handle ensure a positive grip
- Ideal for removing most spin-on type oil filters



T70310 2-15/16" to 3-3/4"

T70311 4" to 4-3/8"

T70317 4-3/4" to 5-3/4"

T70320 2-7/8" to 3-1/4"

T70321 3-1/2" to 3-7/8"

### T70322 Heavy Duty Oil Filter Wrench

- Wide s
- Automatic clamping action, dimpled band for a solid grip
- Fits filters: 2-7/8" to 3-1/8"



T70323 3-5/8" to 3-15/16"

### T70326 Standard Filter Wrench

- Autom
- Easy grip vinyl handle
- Fits filters: 3" to 3-3/4"
- Ideal for removing most truck and tractor filters



T70328 Truck and Tractor Oil Filter Wrench (4" to 4-3/8")

**T70331** Oil Filter Pliers (60-115mm)

- Perfect
- Non-slip adjustable jaws with gripping teeth
- Non-slip, red vinyl handles



**T70332** 9" Oil Filter Pliers (60-90mm)

- Perfect
- Heavy-duty laminated construction
- Serrated jaws with spring loaded adjustment
- Non-slip, cushion grip handles



**T70333** 10" Oil Filter Pliers (60-115mm)

- Perfect
- Heavy-duty laminated construction
- Serrated jaws with spring loaded adjustment
- Non-slip, cushion grip handles



**T70423** Oil Filter Wrench Master Pliers

- Fits dia
- 2-1/8" to 4-5/8" (53-118mm)
- Non-slip, serrated jaws lock in position to remove stubborn oil filters
- Suitable for many other applications



**T70341** Heavy Duty Oil Filter Wrenches

- Design



- Robust, corrosion resistant construction
- Wide band distributes pressure evenly, preventing filter distortion
- Use with a 1/2" Dr. extension

**T70341** 4-1/8" to 4-21/32"

**T70342** 4-21/32" to 5-5/32"

**T70343** 5-5/32" to 5-21/32"

**T70424** Oil Filter Wrench

- Efficient
- operation in confined spaces
- Corrosion resistant, dimpled band adjusts easily via the knurled handle from 2-3/8" - 4.5" (60-110mm)



**T70426** Strap Oil Filter Wrench

- Extra l
- Four styles of non-slip straps
- Up to 6" diameter



## Chain Oil Filter Wrenches

superb gripping action



**T70417**



**T70418**



**T70425**

## T70427 Strap Oil Filter Wrench

• Non-slip

- Universal application for automobiles, tractors and trucks



## T70416 Cup Type Oil Filter Wrench

• 88mm

- Corrosion resistant, black oxide coated
- Designed specifically for Volvo Model S40, S70 & S80
- Use a 3/8" Dr. ratchet wrench for removal or installation



## T75871 11-Piece Cup Type Oil Filter Wrench Set

Includes:



<b>T70401</b>	74/76mm	15 flutes	2 step
<b>T70402</b>	76mm	14 flutes	1 step
<b>T70403</b>	93mm	15 flutes	1 step
<b>T70404</b>	73mm	14 flutes	1 step
<b>T70405</b>	65/67mm	14 flutes	2 step
<b>T70406</b>	68mm	14 flutes	1 step
<b>T70407</b>	80mm	15 flutes	1 step
<b>T70409</b>	90mm	15 flutes	1 step
<b>T70410</b>	80/82mm	15 flutes	2 step
<b>T70411</b>	93mm	36 flutes	1 step
<b>T70412</b>	75/77mm	15 flutes	2 step
<b>T70413</b>	65mm	14 flutes	1 step
<b>T70414</b>	76mm	30 flutes	1 step
<b>T70415</b>	100mm	15 flutes	1 step

and one adaptor - 1/2" Dr. (F) x 3/8" (M)

- Heat-treated, durable steel with black oxide to resist corrosion
- Specially designed for 1 or 2 step models, fitting various flute designs on Fram, AC, Casite, Lee, Hastings, Motorcraft, NAPA, Purolator, STP, Pure One, Wix, as well as some Japanese and European made filters
- Use with 3/8" Dr. ratchet
- Complete oil filter manufacturers reference table included

**T70052** Oil Heater Line Disconnect Tool

- Releases heater hose from engine block and thermostat housing
- Fits 1991 to current GM 3.1L/3.4L and 3800 engines


**T75817** Heater Hose Disconnect Tool

- Disconnects heater hose from heater core tube without damaging hose or coupling retainer
- Works on most Ford and Chrysler vehicles: 1986 to current Aerostar vans, Plymouth and Chrysler vehicles, 1991 to current Ford vans


**T70126** Fin Straightener and Cleaner

- Cleans and straightens radiator fins
- Multi 6-head tool handles: 6, 8, 10, 12, 14, 15 fins per inch



**New**

**T75520** A/C Clutch Spanner Wrench

- Specializes in adjusting A/C clutch
- Adjustable brass thumbscrews
- Bright red, plastic, non-slip handle


**T71190** UV Light Air Conditioning Leakage Tester

- Ideal for detecting leaks in A/C systems
- High powered true UV LED technology
- Push button and turn switch for on and off power
- Uses 3 AA batteries (Not included)
- Insulated, flexible extension cable accesses hard to reach areas



**New**

**T70561** Radiator Tool Set

- Ideal for working on engines, fluid storage tanks, etc.
- Contents: Universal Radiator Petcock Socket, Universal Radiator Drain Plug Socket, Heater and Radiator Hose Slitter


**Includes:**

- 1 - Freeze Plug Removal / Installer Kit

**New**




- 1 - Long installing tool with swivel ball end
- 7 - Adaptors (20, 25, 30, 35, 40, 45, and 50mm)
- Removes freeze plugs up to 2" diameter
- Long installing tool with ball end swivel for easy positioning and reaching stubborn freeze plugs

## T75990 R134a Air Conditioning Manifold Gauge Set (Aluminum Body)

• High q

**New**




Includes:

- Aluminum manifold body with all necessary fittings
- 2 easy-to-read, new silicone vibration-free gauges
- 1 set of 60" hose - Yellow hose with 1/2 ACME x 1/2 ACME with quick seal valve
- Red and blue hoses with 1/2 ACME x 14mm male thread
- Automotive quick coupler-high pressure in red with 14mm female thread
- Low pressure in blue with 14mm female thread

## T75992 R134a Air Conditioning Manifold Gauge Set (Brass Body)

Includes

**New**



- Brass manifold body with all necessary fittings
- 2 easy-to-read, new silicon vibration-free gauges
- 1 set of 60" hose - yellow hose with 1/2 ACME x 1/2 ACME with quick seal valve
- Red and blue hoses with 1/2 ACME x 14mm male thread
- Automotive quick coupler - High pressure in red with 14mm female thread
- Low pressure in blue with 14mm female thread

## T75551 Universal Radiator Pressure Test Kit

• Tests a

- Prevents radiator line leakages and replaces damaged parts

T75551-0 Temperature Thermometer

**New**



T75551-1 Pressure Testing Pump with Gauge  
12 Adaptors:

T75551-2 Works on large trucks, GM

T75551-3 Works on Mercedes, Ford, GM, Jeep and large trucks

T75551-4 Works on Peugeot, Mitsubishi, Nissan, Mazda, Toyota, Subaru, Infiniti, GEO and Suzuki

T75551-5 Works on Honda, Toyota, Suzuki, Mitsubishi

T75551-6 Works on Opel, VW, Ford, BMW245, Saab and Jaguar

T75551-7 Works on Volvo, Saab, Audi, Citron, Renault, Peugeot, Fiat, Alfa, and Jeep

T75551-8 Works on new VW

T75551-9 Works on VWT4, New Audi A4, A5, A6 and BMW345

T75551-10 Works on BMW

T75551-11 Works on Audi, VW

T75551-12 Works on Ford, International, GM and Rover

T75551-13 Works on Mercedes

## T73420 Automatic Coupler Set for R134a Manifolds

• Autom

**New**



on all R134a charge and service ports with various dimensions

- Easy to connect and disconnect, actuation valve for access to system even at working pressure.
- High pressure in red color with 14mm female thread
- Low pressure in blue color with 14mm female thread

**T75950 Deluxe Clutch Hub Puller and Installer Kit**

• Compl

**New**




- GM, Ford, and Chrysler vehicles
- Detailed application chart included

**T75951 A/C Compressor Clutch Service Kit**

• Remov

**New**



- Includes installing adaptors, pulling plate, thrust bearing, fixing screws, and adjustable air conditioning compressor wrench

**T75971 GM Air Conditioning Compressor Seal Set**

• Compl

compressors

- Works on GM A6, R4, late DA6, HR-6, V5, Pole R4



**New**

**T75972 GM DA6 A/C Compressor Seal Set**

• For ca

- Specially designed for GM DA6 air conditioning system



**New**

**T75973 A/C Compressor Seal Service Set**

• Use w

seals on Ford FS6, Chrysler C171, Nippondenso 6P 148A, and Tecumseh HR-980



**New**

**T75974 A/C Seal Set for Ford X-15/FS-10**

• Use w

seals on Ford FX-15/FS-10



**New**



**T75975 Master Air Conditioning Compressor Seal Service Tool**

**New**



**Set**

- Complete tool set replaces air conditioning compressor seals on most domestic and imported vehicles

**T75976 Master Clutch Service Tool Set**

• Compl

**New**



compressor

- Fits: GM A6, R4 and DA; 6 Pole R4, V5 and HR-6; Ford FS6; Chrysler C171; Nippondenso 6p 148A, Sanded 507, 508, and 510; Pitts and warner clutch

**T75977 Air Conditioning Compressor Orifice Tube**

**New**



**Tools**

- Removes and installs most style orifice tube
- Fits GM (CCOT) and Ford (FOTCC) systems with evaporator inlet orifice tube, Ford (FOCC) screen extractor, and Ford

**T75952 Universal Air Conditioning Adapter Set**

• 8pc ad

services

**New**



**Includes:**

- 2 - Automotive shut-off valves-1/4" x 1/4" and 1/4 x 3/16"
- 1 - GM 1991 to current service adapter
- 2 - 1/4" x 3/16" GM flex hose and 1/4" x 1/8" Ford flex hose
- 3 - GM, GM / Ford and GM Large bore disconnectors

**T75954 Safety Air Conditioning Adapter Set**  
 • Service

**New**



Includes:

- 2 - Automotive shut-off valves 1/4" x 1/4" and 1/4" x 3/16"
- 1 - GM 1991 to current service adapter
- 2 - 1/4" x 3 1/6" GM Flex hose and 1/4" x 1/8" Ford flex hose and accessories: Gaskets/O-Ring, Depressors

**T75956 Popular Air Conditioning Adapter Set**  
 • Popular

**New**



- 2 - Automotive shut-off valves 1/4" x 1/4" and 1/4" x 3/16"
- 1 - GM 1991 to late service adapter
- 2 - 90 degree shut-off valves 1/4" x 1/4" and 1/4" x 3/16"
- 2 - Ford and GM large bore quick disconnectors

**T75980 Air Conditioning Pulley Puller**  
 • Special

conditioning compressor pulleys without distorting the components



**New**

**T75965 Air Conditioning Flush Kit**  
 Includes

**New**



**T75960 Air Conditioning System Oil Injector**  
 • Adds r

dyes into the air conditioning system  
 • Includes a low side coupler on the outlet hose (R134a)



**New**

Hose assembly - R134a Charging hose 3000 psi, Burst 600 psi max. working pressure  
 Flush gun assembly

- Special design to work with any light weight flushing solvent that can be mixed with pressurized air
- Do not exceed 150 psi and do not leave pressurized flushing canister unattended